



# SEIKOH GIKEN


## SFP-560A3 High standard Mass production Polishing machine



### ■ Features / Benefits

“SFP-560A3” model offers;

- Consumables info input: Entry of Film, Pad, Liquid info can be done with barcode scanner and touch panel - Manages Film service life
- "Add time" feature manages polishing time as per usage - Provides more uniformed geometry and extend film usage
- Pressure ramp-up and Fixed Height Mode available for each polishing step
- Wider speed adjustment range : 10- 200 rpm
- Network connection by two methods: Modbus TCP/IP



Step	Time (sec)	Speed (rpm)	Ramp Up (sec)	Press. (N)	Ramp Up (sec)
1	30	110	10	100.0	20
2	30	110	10	100.0	20
3	30	110	10	100.0	20
4	30	110	10	100.0	20
5	30	110	10	100.0	20
6	30	110	10	100.0	20
7	30	110	10	100.0	20
8	30	110	10	100.0	20

Interface of A3C model consumables info input & control

### ■ Specifications

*New Technology*  
~DPC : Dynamic Pressure Control~  
(Patent Pending)

Weight	22kg (48.5lb)
Dimensions	240W x 370D x 305H (mm)
Polishing Method	Rotation & Revolution
Pressure Control	2N to 200N in DPC mode
Power	100~ 240 VAC, 50/60Hz
Required Air	0.6MPa to 0.8MPa
Motor speed	Revolution: 10 to 200rpm Rotation: 1/100 of rev. speed
Process storage	48 processes
Film and Pad Size	5" (127mm)



High Volume, Multi-Axis  
Intelligent Automation  
Superior MT Geo.

## SFP-560A3 Standard Package

Description	Part Number	Qty
Main unit	SFP-560A3	1
2A fuse (in fuse holder)	RP55-56	1
M3 x 60-SUS bolt	M14-00096	2
Power cable	RP55-30	1
Cable hanger	FP-CH	1
USB memory	FP-USB	1
Check valve	RP56A-24	1
Barcode scanner	FP-SCN56-A	1
Operation manual	FP-IM56A3	1
Process manual	FP-PM56A3	1
Maintenance manual	FP-MM56A3	1

## Available Polishing Consumables

### POLISHING FILMS FOR ZR POLISHING

Description:	Film Part #
30um Silicon Carbide	GA5D
30um Diamond	EDA5D-30U
9um Diamond	EDR5D-9U
5um Diamond	EDG5D-5U
3um Diamond	EDH5D-3U
1um Diamond	EDJ5D-1U
Silica	XF5D

*\*Other types of films and liquid are also available up on request*

### POLISHING FILMS FOR MT POLISHING

Description:	Film Part #
Adhesive Removal & Leveling	GC5D
Rough polishing	AR5D
Fiber protrusion	GH5D
Finishing	FM5D-SOAP-2

*\*Consumables for slurry polishing are also available upon request*

Rubber & Glass Pads Available for various Hardness & Thickness (*ask for details*):  
 60, 65, 70, 75, 80, 85 & 90 durometer  
 4.8, 4.9, 5.0, & 5.05 mm thickness All for 5" diameter  
 For MT polishing, PG5X-490-SR3, tacky glass pad is available, which PSA backing is no longer needed.

**Find us on YouTube!**

 / SEIKOH GIKEN



## Available Fixtures & Accessories

### I.P.C. HOLDERS

Description:	Holder Part #
FC/PC	PH55-FP-20 or 24
FC/APC (Step or Conical)	PH55-FP8*-18-I or 24
SC/PC	PH55-CP-20, 24 or 32
SC/APC (Step or Conical)	PH55-CP8*-18-I or 24 or 32
ST/PC	PH55-SP-20 or 28
LC/PC Simplex & Duplex	PH55-PL-48DHP or 54DHP
LC/APC High Pressure	PH55-PL8A-48HP or 54HP
LC/APC Duplex	PH55-PL8A-32DHP-POR
<b>VSFF Connectors New</b>	
CS/PC	PH55-CS-20
CS/APC	PH55-CS8A-18
MDC/PC	PH55-MDC-24
MDC/APC	PH55-MDC8A-24
SN/PC	PH55-SN-24
SN/APC	PH55-SN8A-24
MDCJR/APC	PH55-MDCJR8A-24
SNJR/APC	PH55-SNJR8A-24
SNCOM/APC	PH55-SNCOM8A-24
IP16/SN Ferrule / PC	PH55-F0423-700

### FIXED D.P.C. HOLDERS (SFP-560A series only) New

Description:	Holder Part #
Conical SC/APC	PH55-CP8C-16FX
OptiTap	PH55-OPT8C-18FX or 24FX
LC/PC Simplex & Duplex	PH55-PL-32DFX or 48DFX
LC/APC Simplex	PH55-PL8A-24FX or 48FX
LC/APC Duplex	PH55-PL8A-32DFX-POR
MDC/PC	PH55-MDC-24FX
MDC/APC	PH55-MDC8A-24FX
CS/PC	PH55-CS-20FX
CS/APC	PH55-CS8A-18FX
SN/PC	PH55-SN-24FX
SN/APC	PH55-SN8A-24FX
MDCJR/APC	PH55-MDCJR8A-24FX
SNJR/APC	PH55-SNJR8A-24FX
SNCOM/APC	PH55-SNCOM8A-24FX
IP16/SN Ferrule / PC	PH55-F0423-700FX
Universal ferrule holder	PH55-F0423-210C

### MT HOLDERS & ACCESSORIES

Description:	MT Holder Part #
MT/PC One-lever Holder	PH55-MT-24SQ1-B
MT/APC One-lever Holder	PH55-MT8A-24QD <b>New</b>
Washing station	MT-P-WSH56-C
Cable Management	MT-P-CMH56-D
Air Blower	MT-P-BLW56-B
Non-woven cleaning paper	MT-P-NWPAPER-A

*\*Please contact for connector types and capacity not listed.*

*\*Custom made holders are available upon request*

*\*Cable management for IPC holders are also available.*

## WORLDWIDE SUBSIDIARIES AND SALES OFFICES:

### North America

Atlanta, Georgia  
 Tel: +1-770-279-6602  
 Fax: +1-770-279-8839  
[sales@sg-usa.com](mailto:sales@sg-usa.com)

### Europe

Frankfurt, Germany  
 Tel: +49-6102-297-700  
 Fax: +49-6102-297-750  
[info@sg-euro.de](mailto:info@sg-euro.de)

### Asia

Matsudo, Japan  
 Tel: +81-47-388-6111  
 Fax: +81-47-388-4477  
[sales.div@seikoh-giken.co.jp](mailto:sales.div@seikoh-giken.co.jp)

### China

Hangzhou, PROC  
 Tel: +86-571-8777-4098  
 Fax: +86-571-8777-4099  
[sales@sg-h.cn](mailto:sales@sg-h.cn)

Seikoh Giken reserves the right to improve, enhance and modify features and specifications of Seikoh Giken products without prior notifications

 SEIKOH GIKEN

